

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
24 December 2003 (24.12.2003)

PCT

(10) International Publication Number  
WO 03/106976 A1(51) International Patent Classification<sup>7</sup>: G01N 17/02

(21) International Application Number: PCT/GB03/02445

(22) International Filing Date: 6 June 2003 (06.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0213912.9 17 June 2002 (17.06.2002) GB(71) Applicant (for all designated States except US): THE  
UNIVERSITY OF MANCHESTER INSTITUTE OF  
SCIENCE AND TECHNOLOGY [GB/GB]; PO Box  
88, Manchester M60 1QD (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): COTTIS, Robert,  
Alan [GB/GB]; 42 Clement Road, Marple Bridge, Stock-  
port SK6 5AG (GB).(74) Agent: ALLMAN, Peter, John; Marks & Clerk, Sussex  
House, 83-85 Mosley Street, Manchester M2 3LG (GB).(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,  
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,  
UZ, VC, VN, YU, ZA, ZM, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

## Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR MONITORING CORROSION



(57) **Abstract:** A method and apparatus for monitoring the corrosion of a working electrode. An alternating perturbation signal of at least one frequency is applied to the working electrode. A signal representing the response of the working electrode to the applied perturbation signal is monitored. The monitored signal is filtered to separate out a signal representing the response of the electrode to the or each applied frequency and an electrochemical noise output signal representative of corrosion of the working electrode. The potential of the working electrode relative to a reference electrode may be controlled by controlling the supply of current through an auxiliary electrode. The supplied current is then monitored and the monitored current is filtered. Alternatively, a known alternating current may be applied between the working electrode and an auxiliary electrode and fluctuations in the potential of the working electrode relative to a reference electrode may be monitored, the monitored potential being filtered. A measure of the impedance of the working electrode is derived from the applied perturbation signal and the response signal. Both electrochemical potential noise and electrochemical current noise measurements may be derived from the known applied potential and the measured current or the known applied current and the monitored potential.